UL Product iQ®



Heat-automatic Fire Detectors

COMPANY

Fireguard Global Ltd

3 Church St Kidderminster Worcestershire, DY10 2AD United Kingdom

S25225

					Spaci	ng (Ft)
				Temp		to Wall
		Compatibility	Contact	Range	Smooth	or
Model No.	Type	Restrictions	Arrangement	(°F)	Ceiling	Partition
IQ458SH-2 (a), IQ458SH-2M (a), IQ458H-2 (a), IQ458H-2M (a), IQ458SH-2L(a), IQ458SH-2LM (a), IQ458H-2L (a), IQ458H-2LM (a)	FT/ROR	D2	-	-	-	-
IQ458SH-4, IQ458SH-4M, IQ458H-4, IQ458H-4M	FT/ROR	D2	-	-	-	-
IQ568A-H (a), IQ568A-SH (a), IQ568A-HL (a), IQ568A-SHL (a)	FT/ROR	D2	-	-	-	-
IQ568D-H (a), IQ568D-SH (a), IQ568D-HL (a), IQ568D- SHL (a)	FT/ROR	D2	-	-	-	-
IQ651H	FT/ROR	D2	-	135	50	50

Base Model	Related Detector	Control Unit Compatibility Restrictions		
IQ651B	FW511, FW521	В3		
IQ651BL	FW511, FW521	В3		

B3 - For connection to a Listed open area protection smoke or heat detector head with which compatibility was determined by test or a review of circuit parameters. Refer to the manufacturer's installation instructions for a list of compatible models.

FT/ROR - Fixed temperature/rate of rise combination

Trademark and/or Tradename: "FIREGUARD", "FIREGUARD GLOBAL", ,



FIREGUARD / FIREGUARD by Euro Systems-UK / Euro Systems

Last Updated on 2024-01-30

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

D2 - For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.