

Valves | Water Control Valves (OS&Y and NRS Gate Valves) | Gate Valves, Outside Screw and Yoke

Models FGO135, FGO138, FGO907, FGO131

Product Description

Models FGO135, FGO138, FGO907, FGO131 Resilient Seated Gate Valves. Rated Working Pressure of 300 psi (2070 kPa) unless otherwise noted below. Available with the end connections listed below.

Product Specification

Model No	Valve Size		End Connection
	in	(mm)	
FGO135	2 1/2, 3, 4, 6, 8, 10, 12*	(65, 80, 100, 150, 200, 250, 300, 76.1, 165.1)	Groove x Groove
FGO138	2 1/2, 3, 4, 6, 8, 10, 12*	(65, 80, 100, 150, 200, 250, 300, 76.1, 165.1)	Flange x Groove
FGO907	2*, 2 1/2, 3, 4, 6, 8, 10, 12*	(50, 65, 80, 100, 150, 200, 250, 300)	Flange x Flange
FGO131*	2 1/2, 3, 4, 6, 8, 10, 12	(65, 80, 100, 150, 200, 250, 300)	Flange x Flange (BS5136)

* Rated working pressure of 250 psi (1725 kPa)

Details

Category	Gate Valves, Outside Screw and Yoke
Class of Work	1130 - OS&Y and NRS Gate Valves
Approval Standard	FM 1120, 1130 - Fire Service Water Control Valves (OS&Y and NRS Type Gate Valves)
Certification Type	FM Approved
Listing Country	United Kingdom

Company

Fireguard Global Ltd
Unit 11, Chancel Industrial Estate,
Newhall St, Willenhall WV13 1NX,
United Kingdom
<http://fireguard-uk.com>