

DESCRIPTION

Mobile stored pressure ABC powder extinguishers are characterized by their high performance and simple method operation. The ABC Dry Powder Mobile type extinguisher contains high performance powder and thus has achieved highest fire rating. They are suitable for multipurpose application of fires involving free burning materials, flammable liquids, flammable gases and electrical equipment.

Model FGPT-25C/50C comes with external gas cartridge filled with Co2

FEATURE

- Cylinders are made of steel and welded
- Cylinder designed to withstand high pressure and tested at 30 bar.
- High-grade brass head valve ensures reliability and optimizes efficiency.
- Head valves are lever operated.
- High quality wheels to ensure easy mobility.
- High gloss polyester powder painted ensures corrosion resistance.
- Safety valve is fitted in each extinguisher for maximum safety.
- Discharge nozzle designed to produce a precision jet for extinguishing gas.



APPLICATION

- Flammable liquid storage areas
- Airports
- Telephone equipment rooms
- Engine rooms
- Chemical plants and laboratories
- Petrochemical industries
- Spray booths

SPECIFICATION

Model Capacity Type	FGPT-25S 25kg Stored Pressure	FGPT-25C 25kg Cartridge	FGPT-50S 50kg Stored Pressure	FGPT-50C 50kg Cartridge
Outside diameter (mm)	250	300	300	300
Cylinder height (mm)	661	661	918	918
Cylinder weight (kg)	15	15	20	20
Extinguisher weight (kg)	52	52	82	90
Volume (L)	29.5	29.5	59.5	66.5
Filling charge	25kg 40% ABC(EN615)	25kg 40% ABC(EN615)	50kg 40% ABC(EN615)	50kg 40% ABC(EN615)
Temperature (°C)	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C	+5°C~+60°C
Working pressure (bar)	15	15	15	15
Test pressure (bar)	30	30	30	30
Material	HP295	HP295	HP295	HP295
Fire rating	55A IB	55A IB	55A IIB	55A IIB
Packing specification (mm)	450*450*1100	450*450*1100	500*500*1200	500*500*1200