




Model FGPRV115 -1.5" Model FGPRV125- 2.5"

Pressure Restricting Angle valve 300 Lb. Rated Adjustable restriction of residual pressure up to 300 lb. Locking pin device restricts full opening Of valve by untrained personnel, pin may be removed by firefighters to allow full opening of valve.

FEMALE x MALE

Standard equipment:
Female NPT inlet x male hose thread outlet forged brass valve Red hand wheel

Optional Finishes:
PB-Polished Brass
RC-Rough Chrome Plated
PC-Polished Chrome Plated



	A	B	C	D	E
1½"x1½"	100	48	58	123	145
2½"x2½"	127	67	77	165	206

NO	DESCRIPTION	MATERIALS	NO	DESCRIPTION	MATERIALS
1	BODY	ASTM B283 C37700	11	LOCK NUT	ASTM B283 C37700
2	NUT	ASTM B283 C37700	12	HANDLE WHEEL	ZL102
3	WASHER	304	13	WHEEL WASHER	304
4	SEAT SEAL	EPDM(A70)	14	WHEEL NUT	ASTM B283 C37700
5	HOLDER	ASTM B283 C37700	15	COLLAR	ASTM B283 C37700
6	SET SCREW	304	16	WASHER	PA6
7	LOCK NUT	ASTM B283 C37700	17	SET SCREW	304
8	BONNET	ASTM B283 C37700	18	SET NUMBERS	ASTM B283 C37700
9	STEM	ASTM B283 C37700	19	WIRE	304
10	ORING	EPDM(A70)			




Model FGPRV115 -1.5" Model FGPRV125- 2.5"

Pressure Restricting Angle valve 300 Lb. Rated Adjustable restriction of residual pressure up to 300 lb. Locking pin device restricts full opening of valve by untrained personnel, pin may be removed by firefighters to allow full opening of valve.

DOUBLE FEMALE

Standard equipment:
Female NPT inlet and outlet forged brass valve Red hand wheel

Optional Finishes:
PB-Polished Brass
RC-Rough Chrome Plated
PC-Polished Chrome Plated



	A	B	C	D	E
1½"x1½"	100	48	62	123	145
2½"x2½"	127	67	83	165	206

NO	DESCRIPTION	MATERIALS	NO	DESCRIPTION	MATERIALS
1	BODY	ASTM B283 C37700	11	LOCK NUT	ASTM B283 C37700
2	NUT	ASTM B283 C37700	12	HANDLE WHEEL	ZL102
3	WASHER	304	13	WHEEL WASHER	304
4	SEAT SEAL	EPDM(A70)	14	WHEEL NUT	ASTM B283 C37700
5	HOLDER	ASTM B283 C37700	15	COLLAR	ASTM B283 C37700
6	SET SCREW	304	16	WASHER	PA6
7	LOCK NUT	ASTM B283 C37700	17	SET SCREW	304
8	BONNET	ASTM B283 C37700	18	SET NUMBERS	ASTM B283 C37700
9	STEM	ASTM B283 C37700	19	WIRE	304
10	ORING	EPDM(A70)			