

DESCRIPTION

The instantaneous dividing breeching is a simple solution to a common problem so you can take a single water supply and split this into two, with a handy valve on each outlet so you can easily control the flow. With one male inlet and two female outlets, this means a standpipe or hose can then create two hose lines – with a secure fit – giving you double the firefighting power. Manufactured for Vigil Products of a durable light alloy, the inlets and outlets are manufactured to BS336 and is suitable for equipment for 2.5-inch (64mm) diameter hosing. Not just used for fire fighting purposes, the instantaneous dividing breeching is also used for general industrial use, agriculture and irrigation, and wash-down application with a maximum working pressure of 16 bar.

FEATURES

- Manufactured to BS336
- Inlet: 1x 2 ½" Male Instantaneous (BS336)
- Outlet: 2x 2 x 2 ½" Female Instantaneous (BS336)
- For 2.5 inch (64mm) diameter lay flat hosing
- Constructed of light alloy
- Working Pressure: 16 bar



SPECIFICATION

Product	Dividing Breeching 2-Way Lever Controlled
Product Code	VP-FDB65
Dimension	160x300x400mm
Weight	4.64kg
Inlet	1 x 2 ½" Male Instantaneous (BS336)
Outlet	2 x 2 x 2 ½" Female Instantaneous (BS336)
Material	Constructed of light Alloy
Compliance	BS336
Cartoon Quantity	1